



■ CMOS Image Sensors for Digital Cameras/Digital Camcorders

Optical format	Number of record pixels	Color filter	Model No.	Shutter system	Video performance	Resolution	Pixel size H × V (μm)	Sensitivity (mV/Lux-sec) TYP.	Package	
						Image pixels (H × V)				
1 type	12 820 k	R, G, B primary color mosaic filters	RJ5DY1BA0LT	Rolling	10bit 4K2K 60 fps 12bit 4K2K 36 fps	4 144 × 3 096	3.10 × 3.10	1 420	N-LCC120	
		B/W	RJ5DY2BA0LT					2 340		
2/3 type	2 210 k	R, G, B primary color mosaic filters	RJ52N1BA0LT	Rolling	1 080P 120 fps	1 984 × 1 116	5.00 × 5.00	3 520		
		B/W	RJ52N2BA0LT					5 200		
	8 850 k	R, G, B primary color mosaic filters	RJ52V1BA0LT	Rolling	4K2K 60 fps	3 968 × 2 232	2.50 × 2.50	1 780		
		B/W	RJ52V2BA1LT					2 600		
		B/W	RJ52V2BB0LT					3 090		
4/3 type	33 270 k	R, G, B primary color mosaic filters	RJ5EG1BA1LT	Rolling	8K4K 30 fps	7 688 × 4 328	2.45 × 2.45	1 840		N-LGA380
1 type	8 940 k	R, G, B primary color mosaic filters	RJ5D91DA0LT	Global	4K2K 60 fps	4 112 × 2 176	3.45 × 3.45	3 000		N-LGA226A
		B/W	RJ5D92DA0LT					4 380		
2/3 type	5 060 k	R, G, B primary color mosaic filters	RJ52S1DA0LT	Global	1 080P 120 fps	2 464 × 2 056	3.45 × 3.45	3 000	N-LGA226	
		B/W	RJ52S2DA0LT					4 380		
1/1.8 type	3 180 k	R, G, B primary color mosaic filters	RJ51P1DA0LT	Global	1 080P 120 fps	2 064 × 1 544	3.45 × 3.45	3 000		
		B/W	RJ51P2DA0LT					4 380		

Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.

Except where specially indicated, models listed on this page comply with the EU RoHS Directive*. For details, please contact SHARP.

*EU RoHS Directive: EU legislation restricting the use of lead, cadmium, hexavalent chromium, mercury, specific brominated flame retardants (PBB and PBDE), and phthalates (DEHP, BBP, DBP, DIBP).

Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.



High-sensitivity Image Sensors for Security Usage

■ Progressive CCDs

Optical format	Total pixels	Model No.	Video performance	Color filter	Resolution	Pixel size H × V (μm)	Sensitivity*1 (mV) TYP.	Smear ratio (dB) TYP.	Package			
					Image pixels (H × V)							
1/3 type	350 k	RJ33B3AA0DT	VGA 120 fps (1 ch output)	Primary color	660 × 494	7.4 × 7.4	3 000	-125	P-DIP024-0400			
		RJ33B4AA0DT		B/W			4 500					
		RJ33B3AD0DT	VGA 200 fps (2 ch output)	Primary color			3 000					
		RJ33B4AD0DT		B/W			4 500					
	520 k	RJ3331AA0PB	NTSC 650 TV lines	Complementary color	976 × 494	5.0 × 7.4	1 500	-120	P-DIP016-0450			
	610 k	RJ3341AA0PB	PAL 650 TV lines	Complementary color	976 × 582	5.0 × 6.3						
1 350 k	RJ33J3CA0DT	1.3M 30 fps 720p 30 fps (1 ch output)	Primary color	1 320 × 976	3.75 × 3.75	950	-120	P-DIP024-0400				
	RJ33J4CA0DT		B/W			1 430						
1/1.8 type	2 100 k	RJ31N3AA0DT	2M 25 fps (1 ch output)	Primary color	1 644 × 1 236	4.4 × 4.4	1 100	-120	P-DIP028-0566			
		RJ31N4AA0DT		B/W			1 650					
	2 130 k	RJ31N3AD0DT	2M 50 fps (2 ch output)	Primary color			1 100					
		RJ31N4AD0DT		B/W			1 650					
	2 960 k	RJ31P3AD0DT	2.8M 30 fps (2 ch output)	Primary color			1 940 × 1 460			3.69 × 3.69	750	-115
		RJ31P4AD0DT		B/W							1 150	

*1 The average G signal output voltage (the average output voltage in the case of the complementary color filter) when a 1,000-lux light source with a 90% reflector is imaged by a lens of F4 at 1/30 sec (1/25 sec in the case of RJ3341AA0PB) frame accumulation.

Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.

Except where specially indicated, models listed on this page comply with the EU RoHS Directive*. For details, please contact SHARP.

*EU RoHS Directive: EU legislation restricting the use of lead, cadmium, hexavalent chromium, mercury, specific brominated flame retardants (PBB and PBDE), and phthalates (DEHP, BBP, DBP, DIBP).

Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.



Progressive CCDs (cont'd)

Optical format	Total pixels	Model No.	Video performance	Color filter	Resolution	Pixel size H × V (μm)	Sensitivity*1 (mV) TYP.	Smear ratio (dB) TYP.	Package
					Image pixels (H × V)				
2/3 type	5 240 k	RJ32S3AA0DT	5M 9 fps (1 ch output)	Primary color	2 456 × 2 058	3.45 × 3.45	530	-110	P-DIP028-0566
		RJ32S4AA0DT		B/W			800		
		RJ32S3AD0DT	5M 15 fps (2 ch output)	Primary color			530		
		RJ32S4AD0DT		B/W			800		
1/1 type	6 090 k	RJ3DT3AF0DT	6M 30 fps (4 ch output)	Primary color	2 758 × 2 208	4.54 × 4.54	1 150	-125	P-DIP064-1000
		RJ3DT4AF0DT		B/W			1 750		
	8 290 k	RJ3DV3AF0DT	8M 25 fps (4 ch output)	Primary color	3 320 × 2 496	3.88 × 3.88	750	-120	
		RJ3DV4AF0DT		B/W			1 100		
4/3 type	8 340 k	RJ3EV3EF0DT	8M 25 fps (4 ch output)	Primary color	3 848 × 2 168	5.14 × 5.14	1 500	-125	P-DIP064-1000B
		RJ3EV4EF0DT		B/W			2 250		

*1 The average G signal output voltage when a 1,000-lux light source with a 90% reflector is imaged by a lens of F4 at 1/30 sec frame accumulation.

Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.

Except where specially indicated, models listed on this page comply with the EU RoHS Directive*. For details, please contact SHARP.

*EU RoHS Directive: EU legislation restricting the use of lead, cadmium, hexavalent chromium, mercury, specific brominated flame retardants (PBB and PBDE), and phthalates (DEHP, BBP, DBP, DIBP).

Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.



■ 1/3-type CCDs

Total pixels	Standard		Model No.	Resolution		Pixel size H × V (μm)	Sensitivity*1 (mV) TYP.	Smear ratio (dB) TYP.	Package
				Horizontal TV lines	Image pixels (H × V)				
410 k	Color	NTSC	RJ2355DA0PB	480	768 × 494	6.4 × 7.5	2 700	-135	P-DIP016-0450
470 k		PAL	RJ2365DA0PB		752 × 582	6.53 × 6.39			
520 k		NTSC	RJ2331BA0PB	650	976 × 494	5.0 × 7.4	2 400	-125	
610 k		PAL	RJ2341BA0PB		976 × 582	5.0 × 6.3			

*1 The average output voltage measured when imaging a 90% reflector illuminated by a 1,000-lux light source through an optical system set at an f number of F4.0.

■ 1/4-type CCDs

Total pixels	Standard		Model No.	Resolution		Pixel size H × V (μm)	Sensitivity*1 TYP. (mV)	Smear ratio TYP. (dB)	Package
				Horizontal TV lines	Image pixels (H × V)				
410 k	Color	NTSC	RJ2455DA0PB	480	768 × 494	4.9 × 5.6	1 350	-120	P-DIP014-0400A
470 k		PAL	RJ2465DA0PB		752 × 582	5.0 × 4.77			
520 k		NTSC	RJ2431AA0PB	650	976 × 494	3.75 × 5.56	1 400		
610 k		PAL	RJ2441AA0PB		976 × 582	3.75 × 4.74			

*1 The average output voltage measured when imaging a 90% reflector illuminated by a 1,000-lux light source through an optical system set at an f number of F4.0.

Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.

Except where specially indicated, models listed on this page comply with the EU RoHS Directive*. For details, please contact SHARP.
*EU RoHS Directive: EU legislation restricting the use of lead, cadmium, hexavalent chromium, mercury, specific brominated flame retardants (PBB and PBDE), and phthalates (DEHP, BBP, DBP, DIBP).

Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.